



POWERED BY LED INDUSTRIES

PROJECT:
TYPE:

Leijeo Laser



ORDERING INFORMATION

Model	Wattage	Length	Nominal lumen	CRI	CCT	Finish
LI-KH-R-3X132	1- 6W	3 ½"	145lm	1->80	1-2700K	1-WHITE-BLACK 2-BLACK
LI-KH-R-5X132	2- 12.5W	5 ½"	290lm		2-3000K	
LI-KH-R-10X132	3- 19.5W	11 ¼"	530lm		3-3500K	
LI-KH-R-15X132	4- 28W	16 ½"	755lm		4-4000K	
					5-5000K	
					6-6000K	

Optic:


Wall washer,
Wall washer LGC (longitudinal glare control)

Material:

Body: die-cast (zinc/aluminum alloy)
Diffuser: frosted PMMA diffuser with linear optic
Reflector: superpure aluminum
Baffle: polycarbonate)

Rotation:

Tilting adjustability +/-30



Rating:

IP20

Finish:

WHITE-BLACK
BLACK





POWERED BY LED INDUSTRIES

Leijeo Laser

PHOTOMETRIC DATA


LI-KH-R-3X132




LOAD (w)	CCT (K)	CRI	OPTIC	LUMENS	EFFICACY (lm / w)	MAX CANDELA (cd)	MODEL
6W	3000K	80	Wall washer	155	25	125	LI-KH-R-3X132-WW
			Wall washer LGC (longitudinal glare control)	145	24	140	LI-KH-R-3X132-WL

USE MULTIPLIER TABLE BELOW FOR OTHER CCT AND CRI OUTPUT DATA


Wall washer (3000K, 90 CRI)



Wall washer LGC (3000K, 90 CRI)




LI-KH-R-5X132




LOAD (w)	CCT (K)	CRI	OPTIC	LUMENS	EFFICACY (lm / w)	MAX CANDELA (cd)	MODEL
12.5W	3000K	80	Wall washer	290	23	215	LI-KH-R-5X132-WW
			Wall washer LGC (longitudinal glare control)	275	22	270	LI-KH-R-5X132-WL

USE MULTIPLIER TABLE BELOW FOR OTHER CCT AND CRI OUTPUT DATA

Wall washer (3000K, 90 CRI)



Wall washer LGC (3000K, 90 CRI)






POWERED BY LED INDUSTRIES

Leijeo Laser


LI-KH-R-10X132




LOAD (W)	CCT (K)	CRI	OPTIC	LUMENS	EFFICACY (lm / w)	MAX CANDELA (cd)	MODEL
19.5W	3000K	80	Wall washer	530	27	395	LI-KH-R-10X132-WW
			Wall washer LGC (longitudinal glare control)	495	25	485	LI-KH-R-10X132-WL

USE MULTIPLIER TABLE BELOW FOR OTHER CCT AND CRI OUTPUT DATA


Wall washer (3000K, 90 CRI)



Wall washer LGC (3000K, 90 CRI)




LI-KH-R-15X132



LOAD (W)	CCT (K)	CRI	OPTIC	LUMENS	EFFICACY (lm / w)	MAX CANDELA (cd)	MODEL
28.5W	3000K	80	Wall washer	755	26	570	LI-KH-R-15X132-WW
			Wall washer LGC (longitudinal glare control)	715	25	705	LI-KH-R-15X132-WL

USE MULTIPLIER TABLE BELOW FOR OTHER CCT AND CRI OUTPUT DATA

Wall washer (3000K, 90 CRI)



Wall washer LGC (3000K, 90 CRI)

