



POWERED BY LED INDUSTRIES

PROJECT:
TYPE:

Recess Wall Lighting

Application

Recessed wall luminaire with unshielded light distribution. The luminaire has a directing and guiding light effect. The luminance level on the lit surface is lower, but the ambient brightness is greater with increased vertical illuminance.

- **SPECIFICATIONS:**
 - **Material:**
 - Aluminum Alloy
 - Clear safety glass
 - Silicone gasket
 - **Dimensions:**
 - 9 7/8" x 4 7/8"
- **ELECTRICAL:**
 - **Input Voltage:**
 - PoE
 - 277V
 - **Wattage (W):** 11W
 - **Lumens (L)/Watt (W):** 100 l/w
 - **Light Source:** LED
 - **IP:** IP65
 - **Controls:** 0-10V dimming with Poe Driver.
- **FEATURES:**
 - Wooden bulb element can be reversed to illuminate inwards or outwards
 - Light touch dimming control with low, warm, and bright settings
 - 3000K LED light source, Also available in 2700k, 3000k, 3500k, 4000K Color
- **LABELS:**
 - ETL conforms to UL STD 1598; Certified to CAN/CSA STD C22.2
 - LED light assembly conforms to UL 2108 for remote installation.
 - RoHS compliant
- **WARRANTY:**
 - 5-Year Limited Warranty



Model	Watts	Nominal Lumens	CRI	Color Temp	Voltage	Dimmable	Finishes
LI-C1130	11W	1100lm	>80	30 - 3000K 35 - 3500K 40 - 4000K	1-PoE Node 2-100-120V	PD-PoE Dimmable	Black White Silver Bronze