

# Wall Mount

PROJECT:

TYPE:

## Application

Wall luminaire with unshielded light . The luminaire has a directing and guiding light effect. The luminance level on the lit surface is lower, but the ambient brightness is greater with increased vertical illuminance.

- **SPECIFICATIONS:**
  - **Material:**
    - Aluminum Alloy
  - **Dimensions:**
    - 5." W x 6.25" H x 4." Ext
- **ELECTRICAL:**
  - **Input Voltage:**
    - PoE
    - 120V
  - **Wattage (W):** 10W
  - **Lumens (L)/Watt (W):** 100 l/w
  - **Light Source:** LED
  - **IP:** IP65
  - **Controls:** 0-10V dimming with Poe Driver.
- **FEATURES:**
  - ADA compliant, low profile design
  - Up & down light
  - Light touch dimming control with low, warm, and bright settings
  - Available in in 3000k, 3500k and 4000k Color
- **LABELS:**
  - ETL conforms to UL STD 1598; Certified to CAN/CSA STD C22.2
  - LED light assembly conforms to UL 2108 for remote installation.
  - RoHS compliant
- **WARRANTY:**
  - 5-Year Limited Warranty



Model	Watts	Nominal Lumens	CRI	Color Temp	Voltage	Dimmable	Finishes
LI-LMR78	6W	600lm	>80	30 - 3000K 35 - 3500K 40 - 4000K	1-PoE Node 2-100-120V	PD-PoE Dimmable	Black White