

Glider Pendant

Description:

A spatial shape, yet near and tangible, that thrills and inspires a sense of identity through the extraordinary and fantastic. With the help of the plastic injection technology we developed a lighting collection which, through its ribs combined with the geometrical form, immerses us in a world of dreams.

■ SPECIFICATIONS:

■ Material:

- polycarbonate, stainless

■ Dimensions:

- H 11.4" x Ø 41.3"

■ ELECTRICAL:

■ Input Voltage:

- PoE
- 100-277V

■ Wattage (W): 4 x 8W (Maximum)

■ LED Lumens/Watt: 100 LM/W

■ Light Source:

- E27

■ Controls: 0-10V dimming with Poe Driver.

■ LABELS:

- ETL conforms to UL STD 1598; Certified to CAN/CSA STD
- LED light assembly conforms to UL 2108 for remote installation.
- RoHS compliant

■ WARRANTY:

- 5-Year Limited Warranty





POWERED BY LED INDUSTRIES

Glider Pendant

Dimensions:



ORDERING INFORMATION

Ordering Example: LI-GLI-10

Model	Watts	Nominal Lumen	CRI	Color Temp	Voltage	Dimmable	Finish
LI-GLI-10	32W	3200lm	>90	27 - 2700K 30 - 3000K 35 - 3500K	1-PoE-N 2-100-277V	PD-PoE Dim. N-None	White Black

LED Industries reserves the right to change specs or exchange fixtures without further notice

Page 2 of 2